



Matagami Camp

Producing and Historical Production

	<u>Deposit</u>	<u>Production</u>	<u>(Mt)</u>	<u>% Zn</u>	<u>% Cu</u>	<u>Ag g/t</u>	<u>Au g/t</u>	<u>Depth(m)</u>
South Flank	Matagami Lake	1963-1988	25.64	8.20	0.56	20.91	0.41	30 - 228
	Orchan	1963-1982	4.51	9.84	1.02	37.03	0.51	31 - 366
	Isle Dieu	1989-1997	3.05	17.85	1.01	76.63	0.46	320 - 610
	Bell Allard South	1968-1970	0.23	9.24	1.14	37.03	0.51	18 - 70
	Bell Allard	1999-2004	3.59	13.67	1.25	40.55	0.69	950 - 1025
	Perseverance (Xstrata)	2008-	5.12	15.82	1.24	29.00	0.38	30 - 300
North Flank	Norita	1976-1997	3.89	3.94	1.83	25.84	0.59	10 - 689
	Norita East	1992-1996	1.08	10.21	0.80	41.42	0.74	600 - 900
	New Hosco	1963-1970	1.83	1.73	1.73	10.29	0.34	9 - 305
	Garon Lake	1968-1970	0.47	2.17	1.46	10.29	0.34	15 - 250
	Radiore 2	1979-1980	0.14	1.34	1.57	8.57	0.31	Surface

Resources

South Flank	Bracemac McLeod	Indicated	3.62	11.52	1.60	31.55	0.49	50 - 900
	(NI43-101 compliant)	Inferred	0.51	1.28	1.85	11.17	0.18	
<u>Historical resources reported in the public domain – Not NI43-101 Compliant</u>								
South Flank	Orchan West (Historical)*		0.34	15.86	1.72	29.65	0.46	1050 - 1150
West Camp	Phelps Dodge (Historical)**		1.43	5.30	0.95	19.90	N/C	15 - 450
	Cavalier Zone 3 (Historical)***		0.29	1.40	1.48	11.94		50

* Noranda 1997, internal report, based on 12 mineralized holes, 15 confining holes - 30m average drill spacing. "Indicated Mineral Resource" reported.

** Normand Lécuyer Enterprise Inc. and D.R. Melling Geological Consulting Feb. 1991, based on 27 mineralized holes, 18 confining holes, 30m average drill spacing, "Probable Geological Reserve" reported, category does not conform to 43-101 definitions.

*** Phelps Dodge 1998 – 1998 published assessment report (GM58042) – based on 3 exploration drill holes, no classification provided - exploration data only